


## 2444 Baldwin Road, Cleveland, OH 44104 800.662.6338 PSS-Innovations.com



#### Lanedard o folded is shown at

### DEPLOY, FOLD, AND STORE

LaneGard 3<sup>™</sup> folds for transport and storage, with PSS Wave Centerboards attached. Unfolds for deployment.

When deployed LaneGard 3 uprights has a footprint of 46"x48" and is 64" tall. The true width of LaneGard 3 will depend on how long of Wave CenterBoards are mounted on it. Wave CenterBoards are available in 4', 6', and 8' lengths. When folded, LaneGard is 48"x73.75"x2.562".

Patents: http://bit.ly/3cHVTp8

# LANEGARD3<sup>™</sup> FOLDING TYPE III BARRICADE



### **LANEGARD FEATURES**

- » Made from engineered plastic with UV inhibitors.
- » Weighs 17 lbs. assembled, without cernterboards.
- » Molded-in Warning Light Mount accepts LED Warning Lights.
- » Molded through-holes recessed for flushmounted hardware.
- » Designed for use with PSS Wave Centerboards. PSS Wave Centerboard available in 4', 6', 8' lengths.
- » Retroreflective sheeting meets all state and federal specifications. Available in Engineer,Hi-Intensity and Diamond grades.
- » Anti-Skid Feet, two per cross-bar.





1.

2.

# LANEGARD<sup>®</sup> 3 UPRIGHT FEATURES:

LaneGard 3 folds for transport and storage and unfolds for use with PSS Wave Centerboards attached. Measures less than 3" thick when folded. Once assembled, always assembled.

- 1. Molded-in Warning Light Mount accepts LED warning lights.
- Molded through-holes recessed for flushmounted hardware.
- Use sandbags or PSS tire collars for additional ballast.
- Anti-Skid Feet can provide additional stability
  Two per crossbar.

FHWA LETTER: Letter: WZ-336 Tested to Manual for Assessing Safety Hardware (MASH) Test Level: 3



# LANEGARD<sup>™</sup> 3 FEATURES:

One-piece design folds for storage and transport and unfolds for use. Sets up and tears down in seconds. One person can easily fold and unfold LaneGard 3 for transport and deployment. Weighs 17 lbs without centerboards.

LaneGard 3 is designed for use with PSS Wave<sup>™</sup> Centerboards. Available in 4', 6', and 8' lengths. Retroreflective sheeting is available in Engineer, Hi-Intensity, and Diamond Grades. Retroreflective sheeting meets all state and federal specifications. Wave accepts sheeting on one or both sides.





PSS | 2444 Baldwin Road, Cleveland, OH 44104 | 800.662.6338 | PSS-Innovations.com | Copyright © 2024 01/24

Safer Roads Save Lives

We are a proud member of: